









# BUILT TO LAST

### 1 CHASSIS

The durable double-cradle frame of the Brute Force® 750 4x4i ATV is reinforced for added strength. Independent double wishbone front suspension, and double A-arms in the rear carry preload-adjustable shocks providing 6.7 inches of travel up front and 7.5 in the rear for a comfortable ride.

### **2 STOPPING POWER**

Dual disc brakes with two-piston calipers in the front and Kawasaki's sealed, oil-bathed multi-disc brake system in the rear add up to exceptional stopping power. Paired with the electronic Kawasaki Engine Brake Control, you can take on descents with confidence.

### **3 ROUGH TERRAIN CAPABILITY**

A short wheelbase, tight turning radius (10.5 feet), and 9.4 inches of ground clearance combine for exceptional maneuvering and capability. A generous 1,250-pound towing capacity and two-inch receiver hitch adds to the capabilities of the Brute Force 750 4x4i ATV, making it an asset for any homesteader.





BRUTE FORCE® 750 4x4i

## DESIGNED FOR COMFORT





### OUTMUSCLETHE OUTDOORS

TACKLE EVERY ADVENTURE WITH THE BRUTE FORCE® 750 4x4i EPS & BRUTE FORCE 750 4x4i EPS CAMO



### **BRUTE FORCE 750 4x4i EPS**

### **EXCLUSIVE FEATURES**

- > MODEL-EXCLUSIVE, PREMIUM METALLIC FLAT RAW GRAYSTONE PAINT
- > SPEED-SENSITIVE ELECTRIC POWER STEERING (EPS)



### BRUTE FORCE 750 4x4i EPS CAMO

### **EXCLUSIVE FEATURES**

- > REALTREE XTRA® GREEN CAMO BODYWORK
- > SPEED-SENSITIVE ELECTRIC POWER STEERING (EPS)



REALTREE XTRA® GREEN CAMO



Realtree APG-XTRA Camouflage Design
© 2012 of Jordan Outdoor Enterprises, Ltd., all rights reserved.







### **POWERPLAY**



SUPER BLACK



### CAPABILITY





2017 BRUTE FORCE® FAMILY KAWASAKI GENUINE

### **ACCESSORIES**<sup>†</sup>



### **CUSTOMIZATION IS KEY**

Bring out the best in your Brute Force® ATV with a wide range of Kawasaki Genuine Accessories. The entire range of accessories are made specifically for your Brute Force ATV, to give you easy installation and an integrated fit.

- 1 WINDSHIELD
- 2 STORAGE (FRONT AND BACK)
- 3 CENTER MOUNT PLOW SYSTEM
- 4 54-INCH PLOW BLADE
- 5 WARN® PROVANTAGE™ 3500 WINCH AND WINCH MOUNT
- **6** PROTECTION SKID PLATES



CHECK OUT KAWASAKI.COM OR VISIT YOUR LOCAL DEALER TO VIEW ALL ACCESSORIES.

Accessories and pricing available online



<sup>1</sup>Kawasaki warrants most accessories for 90 days from the date of purchase. Premium Audio system components are warrantied for one (1) year.



### BRUTE FORCE 750 4x4i & BRUTE FORCE 300 FEATURES



### BRUTE FORCE® 750 4x4i FEATURES •

- > Rugged and powerful performance for work and play
- > Powerful fuel-injected 749cc V-twin engine
- > CVT with high/low range, selectable 2WD/4WD with variable front differential control
- > 4-wheel drive capability for climbing, hauling and towing
- > Durable and low-maintenance for lasting performance
- > 1,250-pound towing capacity with 2-inch pickup-truck-style receiver
- > Durable double-cradle frame reinforced for rugged handling
- > Sport-capable 4-wheel independent suspension
- Dual disc front brakes and sealed, oil-bathed multi-disc brake system in rear
- > Bright dual 35W halogen headlights
- > Cargo racks with integrated tie-down hook loops, front storage compartment and
- > Illuminated multi-function digital instrumentation console and 12V accessory outlet

### **EPS FEATURES**





- > Premium Metallic Flat Raw Graystone paint (Optional)
- > Speed-sensitive Electric Power Steering (EPS)

### **EPS CAMO FEATURES**

> Realtree Xtra® Green Camo bodywork

### **COLORS**





**BRUTE FORCE 300** 

### **BRUTE FORCE® 300 FEATURES**



- Compact mid-size performance for work and play
- Powerful, sporty 271cc single-cylinder engine
- CVT with centrifugal clutch
- Rugged style and durable chassis for climbing, hauling and towing
- 500-pound towing capacity with 2-inch pickup-truck-style receiver hitch
- Heavy-duty steel-tube frame for rugged handling
- Sport-capable double-wishbone independent front suspension
- Dual disc front brakes and single-disc rear with parking brake
- Bright dual 35W halogen headlights
- Cargo racks with integrated tie-down hook loops, front storage compartment, full floorboards and 12V accessory outlet
- Illuminated multi-function digital instrumentation console and 12V accessory outlet

### **COLORS**







### BRUTE FORCE° 750 4x4i & BRUTE FORCE° 300 SPECS

	BRUTE FORCE® 750 44	BDUTE FORCE® 750 4-4: 500	DDUTE FORCE® 750 4:-4: 500 04440
	BRUTE FORCE® 750 4x4i	BRUTE FORCE® 750 4x4i EPS	BRUTE FORCE® 750 4x4i EPS CAMO
ENGINE	4-stroke, V-twin, SOHC, liquid-cooled	4-stroke, V-twin, SOHC, liquid-cooled	4-stroke, V-twin, SOHC, liquid-cooled
DISPLACEMENT	749cc	749cc	749cc
BORE X STROKE	85.0 x 66.0mm	85.0 x 66.0mm	85.0 x 66.0mm
COMPRESSION RATIO	9.3:1	9.3:1	9.3:1
MAXIMUM TORQUE	42.7 lb-ft @ 4750 rpm	42.7 lb-ft @ 4750 rpm	42.7 lb-ft @ 4750 rpm
FUEL SYSTEM	DFI® with two 36mm throttle bodies	DFI® with two 36mm throttle bodies	DFI® with two 36mm throttle bodies
IGNITION	Digital DC-CDI	Digital DC-CDI	Digital DC-CDI
TRANSMISSION	2-Speed automatic, reverse	2-Speed automatic, reverse	2-Speed automatic, reverse
FINAL DRIVE	Selectable 4WD with variable front differential control, shaft	Selectable 4WD with variable front differential control, shaft	Selectable 4WD with variable front differential control, shaft
FRONT SUSPENSION / WHEEL TRAVEL	Double wishbone/6.7 in	Double wishbone/6.7 in	Double wishbone/6.7 in
REAR SUSPENSION / WHEEL TRAVEL	Full independent, dual A-arm/7.5 in	Full independent, dual A-arm/7.5 in	Full independent, dual A-arm/7.5 in
FRONT TIRE	AT 25 x 8-12	AT 25 x 8-12	AT 25 x 8-12
REAR TIRE	AT 25 x 10-12	AT 25 x 10-12	AT 25 x 10-12
FRONT BRAKES	Dual hydraulic 200mm discs with 2-piston calipers	Dual hydraulic 176mm discs with 2-piston calipers	Dual hydraulic 200mm discs with 2-piston calipers
REAR BRAKES	Sealed, oil-bathed, multi-disc	Sealed, oil-bathed, multi-disc	Sealed, oil-bathed, multi-disc
GROUND CLEARANCE	9.4 in	9.4 in	9.4 in
STARTING SYSTEM	Electric	Electric	Electric
FUEL CAPACITY	5.0 gal	5.0 gal	5.0 gal
TURNING RADIUS	10.5 ft	10.5 ft	10.5 ft
TOWING CAPACITY	1250 lb	1250 lb	1250 lb
TOTAL RACK CAPACITY	242.0 lb	242.0 lb	242.0 lb
RACK CAPACITY, FRONT/REAR	88.0 lb/176.0 lb	88.0 lb/176.0 lb	88.0 lb/176.0 lb
LIGHTING	35W headlights, 5W taillight, 21W stoplight	35W headlights, 5W taillight, 21W stoplight	35W headlights, 5W taillight, 21W stoplight
FRAME TYPE	Double-cradle, high-tensile tubular steel	Double-cradle, high-tensile tubular steel	Double-cradle, high-tensile tubular steel
TRACK FRONT/REAR	36.4/35.0 in	36.4/35.0 in	36.4/35.0 in
OVERALL LENGTH	86.4 in	86.4 in	86.4 in
OVERALL WIDTH	46.5 in	46.5 in	46.5 in
OVERALL HEIGHT	48.0 in	48.0 in	48.0 in
SEAT HEIGHT	35.8 in	35.8 in	35.8 in
CURB WEIGHT	688.0 lb**	699.0 lb**	699.0 lb**
WHEELBASE	50.6 in	50.6 in	50.6 in
INSTRUMENTS	Speedometer, odometer, dual trip meters, fuel gauge, engine temp, clock, hour meter and 2WD/4WD icon, plus indicators for neutral, reverse, belt, and oil pressure	Speedometer, odometer, dual trip meters, fuel gauge, engine temp, clock, hour meter and 2WD/4WD icon, plus indicators for EPS, neutral, belt, and oil pressure	Speedometer, odometer, dual trip meters, fuel gauge, engine temp, clock, hour meter and 2WD/4WD icon, plus indicators for EPS, neutral, belt, and oil pressure
COLOR CHOICES	Timberline Green	Super Black, Firecracker Red, Metallic Flat Raw Graystone (JHF)	Realtree Xtra® Green Camo
WARRANTY	12 Month Limited Warranty	12 Month Limited Warranty	12 Month Limited Warranty
KAWASAKI PROTECTION PLUS™ (OPTIONAL)	12, 24, 36, or 48 months	12, 24, 36, or 48 months	12, 24, 36, or 48 months

<sup>\*\*</sup>Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). Specifications subject to change.

### BRUTE FORCE® 300

	BRUTE FORCE® 300	
ENGINE	4-stroke, 1-cylinder, SOHC	
DISPLACEMENT	271cc	
BORE X STROKE	72.7 x 65.2mm	
COMPRESSION RATIO	11.0:1	
MAXIMUM TORQUE	15.9 lb-ft @ 6500 rpm	
FUEL SYSTEM	Keihin CVK32 carburetor	
IGNITION	DC-CDI	
TRANSMISSION	2-speed automatic, reverse	
FINAL DRIVE	2WD, Shaft	
FRONT SUSPENSION / WHEEL TRAVEL	Double wishbone/5.2 in	
REAR SUSPENSION / WHEEL TRAVEL	Swingarm/5.6 in	
FRONT TIRE	AT 22 x 7-10 Maxxis tubeless	
REAR TIRE	AT 22 x 10-10 Maxxis tubeless	
FRONT BRAKES	Dual 180mm discs	
REAR BRAKES	Single 180mm disc	
GROUND CLEARANCE	6.1 in	
STARTING SYSTEM	Electrical with recoil backup	
FUEL CAPACITY	3.2 gal	
TURNING RADIUS	9.2 ft	
TOWING CAPACITY	500 lb	
TOTAL RACK CAPACITY	110 lb	
RACK CAPACITY, FRONT/REAR	44 lb/66 lb	
LIGHTING	(2) 35W headlights, 5W taillight and 21W stoplight	
FRAME TYPE	Double cradle, steel	
TRACK FRONT/REAR	33.5/32.7 in	
OVERALL LENGTH	75.4 in	
OVERALL WIDTH	42.5 in	
OVERALL HEIGHT	46.1 in	
SEAT HEIGHT	33.3 in	
CURB WEIGHT	535.8 lb**	
WHEELBASE	45.9 in	
INSTRUMENTS	Speedometer, odometer, clock, fuel gauge and coolant temp light	
COLOR CHOICES	Super Black, Timberline Green	
WARRANTY	12 Month Limited Warranty	

BRUTE FORCE® 750 4x4i EPS

\*\*\*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).

Specifications subject to change.

12, 24, 36, or 48 months

KAWASAKI PROTECTION PLUS™ (OPTIONAL)



## SMALL BUT MIGHTY

### 1 PERFECT FOR KIDS

Get your kids off to the right start aboard Kawasaki's youth-sized KFX® ATVs. The air-cooled four-stroke engine starts with the push of a button and the smooth, reliable power is ideal for learning riders. The CVT means no shifting, so young riders can focus on throttle and brake control.

### **2 POWERFUL BRAKES**

The KFX90 and KFX50 can slow down in a hurry with two front drum brakes and a rear disc brake. All three brakes are operated by handlebar-mounted levers. At foot level, full-length floorboards enable better rider balance and help keep little feet protected.

3

### **3 PARENTAL CONTROLS**

Parents can supervise the start of the vehicle with the help of a keyed ignition while a throttle limiting screw enables them to restrict throttle opening to keep speeds matched to operator skill level. A collar in the Continuously Variable Transmission (CVT) can easily be removed for increased speed as riders gain experience.





### KFX°90 & KFX50 FEATURES





- > Small-size performance, ideal for new riders
- > Parental controls help the vehicle match the operator skill level
- > Low maintenance and lightweight
- 89cc 4-stroke air-cooled engine
- Reliable electric start with keyed ignition and a back-up kick starter
- > Limiting throttle screw enables parents to restrict speeds
- > Automatic transmission (CVT) requires no shifting
- › Adjustable collar in CVT can be removed for higher speeds
- Twin shock absorbers in front, swingarm with single shock in rear
- 8-inch wheels with 18-inch tires
- 2 drum brakes in front and single disc brake in rear
- > Full floorboards to help protect riders' feet

### **COLORS**





### **KFX®50 FEATURES**

- > Small-size performance, ideal for new riders
- > Parental controls help the vehicle match the operator skill level
- › Low maintenance and lightweight
- > 49.5cc 4-stroke air-cooled engine
- > Reliable electric start with keyed ignition and a back-up kick starter
- > Limiting throttle screw enables parents to restrict speeds
- > Automatic transmission (CVT) requires no shifting
- › Adjustable collar in CVT can be removed for higher speeds
- > Twin shock absorbers in front, swingarm with single shock in rear
- > 7-inch wheels with 16-inch tires
- > 2 drum brakes in front and single disc brake in rear

### **COLORS**



LIME GREEN



### KFX° 90 & KFX° 50 SPECS

	KFX®90	KFX®50
ENGINE	4-stroke, forced-air cooled, single	4-stroke, air-cooled, single
DISPLACEMENT	89cc	49.5cc
BORE X STROKE	47.0 x 51.8mm	39 x 41.4mm
COMPRESSION RATIO	10.0:1	10.0:1
MAXIMUM TORQUE	N/A	N/A
FUEL SYSTEM	Mikuni PTE 16	Keihin PTE 16
IGNITION	Solid state CDI	Solid state CDI
TRANSMISSION	Continuously Variable Automatic	Continuously Variable Automatic
FINAL DRIVE	Chain	Chain
FRONT SUSPENSION / WHEEL TRAVEL	Single A-arm with twin shock absorbers/2.8 in	Single A-arm with twin shock absorbers/2.8 in
REAR SUSPENSION / WHEEL TRAVEL	Swingarm with single shock absorber/2.9 in	Swingarm with single shock absorber/2.9 in
FRONT TIRE	AT 18 x 7-8 tubeless	AT 16 x 8-7 tubeless
REAR TIRE	AT 18 x 9-8 tubeless	AT 16 x 8-7 tubeless
FRONT BRAKES	Dual mechanical drums	Dual mechanical drums
REAR BRAKES	Hydraulic discs	Hydraulic discs
GROUND CLEARANCE	At rear axle - 3.9 in	At rear axle - 3.3 in
STARTING SYSTEM	Electric with back-up kick-starter	Electric with back-up kick-starter
FUEL CAPACITY	1.5 gal	1.5 gal
TURNING RADIUS	8.7 ft	8.7 ft
TOWING CAPACITY	N/A	N/A
TOTAL RACK CAPACITY	N/A	N/A
RACK CAPACITY, FRONT/REAR	N/A	N/A
LIGHTING	N/A	N/A
FRAME TYPE	Double cradle, steel	Double cradle, steel
TRACK FRONT/REAR	26.8/26.0 in	27.2/27.6 in
OVERALL LENGTH	56.1 in	55.1 in
OVERALL WIDTH	35.6 in	34.7 in
OVERALL HEIGHT	36.4 in	35.8 in
SEAT HEIGHT	25.6 in	25.0 in
CURB WEIGHT	266.8 lb**	245.0 lb**
WHEELBASE	38.0 in	38.0 in
INSTRUMENTS	N/A	N/A
COLOR CHOICES	Lime Green, Bright White	Lime Green, Bright White
WARRANTY	12 Month Limited Warranty	12 Month Limited Warranty
KAWASAKI PROTECTION PLUS™ (OPTIONAL)	12, 24, 36, or 48 months	12, 24, 36, or 48 months

<sup>&</sup>quot;Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). Specifications subject to change.



### **KAWASAKI STRONG**

### **MUCH MORE THAN MOTORCYCLES**



### **BULLET TRAINS**

You already know KHI builds machines that move people. But, did you know it also builds machines that move thousands of people—all at once? We're talking trains here. From New York City subway cars to Japan's hyper-speed bullet trains, Kawasaki has been in the business since 1906. Whether a 186-mph bullet train or a 1,441cc Ninja® ZXTM-14R motorcycle, KHI likes to believe that the technology that goes into moving thousands of people has a positive effect on how it goes about moving just one.

### MOTORCYCLES

Since KHI built its first motorcycle engine in 1953, it has never stopped pushing technology to arm riders with what they need to dominate the streets. Advanced engineering, exhaustive testing and tireless passion go into every motorcycle every time rubber hits the road. From industry-first features to the features that have evolved over a long history, KHI's innovations will never stop feeding the insatiable appetites of riders around the world.

### ROBOTICS

If robots are the future, then KHI has been shaping it since 1969 when the company built its first industrial robot. KHI continues to be a leader in the development of robots for a diverse number of processes including: assembly, handling, welding, painting and sealing. Kawasaki robot technology is being used every day to manufacture motorcycles and other products.



### **KAWASAKI HEAVY INDUSTRIES, LTD. (KHI)**

With 130 years of Kawasaki Heavy Industries, Ltd. (KHI) engineering building the heaviest, most durable and complex machines on the planet, Kawasaki STRONG is a name we can claim. KHI builds tunnel-boring machines that connect continents and trains that carry millions of New Yorkers in and out of the city 24 hours a day, seven days a week. From these engineering monsters to the last bolt on the Brute Force® 750 4x4i EPS, KHI engineering says, over and over: Use me. Rely on me. I'm built to work.



