

 **YAMAHA**
RACING

*the dark Side
of Japan*

*The call of
the BLUE*



MT-15

THE DARK WARRIOR

WITH **ABS**

Specifications

Engine

Engine type	Liquid cooled, 4-stroke, SOHC, 4-valve
Displacement	155 cm ³
Bore x stroke	58.0 mm × 58.7 mm
Compression ratio	11.6 : 1
Maximum power	14.2 kW (19.3 PS) @10,000 RPM
Maximum torque	14.7 N·m (1.5 kgf·m) @8,500 RPM
Lubrication system	Wet sump
Clutch type	Wet, Multiple-disc
Fuel system	Fuel Injection
Ignition system	TCI (transistor controlled ignition)
Starter system	Electric
Transmission system	Constant Mesh, 6-speed
Final drive	Chain

Chassis

Frame	Deltabox
Front suspension system	Telescopic fork
Rear suspension system	Swingarm (link suspension)
Wheel travel (Front)	130 mm
Wheel travel (Rear)	97 mm
Trail	88 mm
Front brake (ABS)	Hydraulic single disc (282 mm)
Rear brake	Hydraulic single disc (220 mm)
Front tire	100/80-17M/C 52P (Tubeless)
Rear tire	140/70-17M/C 66H (Tubeless)

Dimensions

Overall length	2,020 mm
Overall width	800 mm
Overall height	1,070 mm
Seat height	810 mm
Wheel base	1,335 mm

Dimensions

Minimum ground clearance	155 mm
Curb weight	
(including full oil and fuel tank)	138 kg
Fuel tank capacity	10L/2.6usgal/2.2Imp.gal
Engine oil capacity	1.05 L (1.11 US qt, 0.92 Imp.qt)

Other Information

Spark plug model	NGK/MR8E9
Battery voltage/capacity	12V,4.0Ah(10HR)
Battery type	ETZ-5
Primary reduction ratio	3.042 (73/24)
Secondary reduction ratio	3.714 (52/14)
Shift type	Return
Gear ratio-1st gear	2.833 (34/12)
Gear ratio-2nd gear	1.875 (30/16)
Gear ratio-3rd gear	1.364 (30/22)
Gear ratio-4th gear	1.143 (24/21)
Gear ratio-5th gear	0.957 (22/23)
Gear ratio-6th gear	0.840 (21/25)
Rim size (Front)	17M/C × MT2.5
Rim size (Rear)	17M/C × MT4.0
Inner tube diameter of front fork	41.0 mm
Headlight	LED
Auxiliary light	LED
Brake/tail light	LED
Turn signal light (Front)	12V, 10W × 2
Turn signal light (Rear)	12V, 10W × 2
Speedometer	Digital
Tachometer	Digital
Fuel gauge	Digital
ABS	Single Channel

Colours

Dark Matt Blue



Metallic Black



Features

Bi Functional LED Headlight



Negative LCD Display with Gear Shift Indication



Raised LED Tail Light




Single Channel ABS



155cc Liquid Cooled 4V SOHC FI Engine



Assist & Slipper Clutch



Variable Valve Actuation (VVA)

VVA
VARIABLE VALVE ACTUATION



2yrs / 30,000kms warranty*
3yrs / 40,000kms extended warranty**



"The specifications and design of the motorcycles shown here may vary according to the requirements and are subject to change without prior notice. Colours shown may not match the actual colour due to printing limitations. *Conditions Apply. **Warranty Extended for Engine, FI System, AIS System and Electrical including Wiring harness. 5 years warranty is applicable only in case of purchase of Yamaha protection plus policy during validity period, please refer the protection plus policy for details."

Yamaha Motor India Sales Pvt. Ltd, AKDR Tower - 5th Floor, Door No, 3/381, Rajiv Gandhi Salai (OMR), Mettukuppam, Chennai - 600 097
Phone: 044-3814 7000, Toll Free No.: 1800 420 1600, Email: info@yamaha-motor-india.com

www.yamaha-motor-india.com/motorcycle-mt15.html | f Follow us on www.facebook.com/yamahamotorindia

Authorised Dealer