





No other line of motocross bikes is committed to winning like KX™. We build to win, plain and simple. Decades of racing experience, engineering and technology have led to the most iconic name in Motocross and Supercross. When you ride KX, you ride in the company of legends.

KX™ Overview	4 - 5
KX™450	6 - 9
KX™250	10 - 15
Team Green™	16 - 17
KX™100	18 - 19
KX™85	20 - 21
KX™65	22 - 23
KX™ SPECS	44 - 45

AND BEYOND





LEGACIES ARE NOT BORN OVERNIGHT

Over decades of winning, Kawasaki KX™ motorcycles have gained the reputation of The Bike That Builds Champions. The most storied franchise in the sport of motocross continues today and has no plans of stopping.



















CHASSIS & ERGONOMICS

Feel the race-winning advantage of the Kawasaki KX™450 motorcycle's lean chassis. A rigid and lightweight aluminum perimeter frame contributes to agile handling while EGRO-FIT® handlebar and footpeg adjustability lets you tailor your ride to your preference.

POWERFUL ENGINE

Crafted with the same design used by Kawasaki factory race teams, the 449cc engine produces broad torque and strong, responsive power across the rev range.











STRONGER BRAKES

High-rpm power calls for superior stopping power. In the front, an oversized 270mm
Braking® petal disc and dual-piston caliper with upgraded brake pad materials offer improved feel for increased braking performance. In the rear, a new larger-diameter 250mm Braking petal disc and new lighter-weight master cylinder deliver stronger stopping power.

MORE AGILE CHASSIS

Lightweight balance is the focus of the KX™250 motorcycle's slim aluminum perimeter frame—revised rigidity helps ensure smoother rear shock performance and optimum traction while Kawasaki class-leading ERGO-FIT® adjustability allows you to find your optimal fit and comfort with four-way adjustable handlebar positions and two footpeg positions to choose from.











TEAM GREEN LIFESTYLE

THE FUTURE IS NOW

Behind the glory of every pro champion lies a storied career of a young racer who fought and clawed their way through the amateur ranks. Our roots run deep in motocross, and for 38 years, the Kawasaki Team Green™ program has been shaping new riders into future champions.

Through Kawasaki's industry-leading contingency and racer support program, Team Green™ offers unmatched trackside assistance at local, regional and national amateur motocross, as well as online "factory" support.

Kawasaki continues to forge a tradition for those who ride the legendary KX[™] motorcycle. Kawasaki Team Green[™] racing has given rise to many champions over the past decades and one thing remains proven: KX wins.



KX™100

STEP INTO THE LEGACY

For those who want to take their ride to the next level. This is the last step before the big leagues, so let your rider race hard and take the track by storm with super-mini wheels and power.



POWERFUL BRAKES

A front 220mm petal disc rotor and a rear 184mm petal disc rotor provide premium stopping power. The petal design reduces unsprung weight and helps the brake pads stay clean and cool.

ADJUSTABLE SUSPENSION

The front 36mm inverted cartridge fork houses 20-way adjustable compression damping while the rear Uni-Trak® single shock system features adjustable compression, rebound and preload.





PROPORTIONATE POWER

A 99cc liquid-cooled two-stroke engine provides strong super-mini class power while carbon fiber reed valves and the KIPS® power valve deliver instant power on demand.



RIDE WITH GREATNESS

When your rider goes green, they ride with the best of the best. The KX™85 motorcycle is a championship-proven platform to give your rider the competitive edge with the proportionate performance and durability needed to finish first.



HIGH-PERFORMANCE ENGINE

An 84cc two-stroke engine with a close ratio six-speed transmission and manual clutch allows young riders to get maximum performance out of every ride.



ADJUSTABLE SUSPENSION

A 36mm inverted cartridge fork features adjustable compression damping while the rear Uni-Trak® single shock system offers a fully adjustable KYB shock.

IDEAL ERGONOMICS

Customize the riding position with the ERGO-FIT® system, featuring a six-position adjustable handlebar mount to tailor ergonomics for a wide range of riders.





TOOLS FOR SUCCESS

Jam-packed with everything needed to succeed on the track, this mini-moto bike allows riders to gain experience and build skills on the platform that builds champions.



HIGH-PERFORMANCE ENGINE

A liquid-cooled two-stroke 64cc engine paired with a six-speed transmission produces instant throttle response and power through the entire rev range.

TAME THE TRACK

A 33mm conventional fork features four-position adjustable rebound damping while a rear Uni-Trak® link-mounted shock offers adjustable spring preload and rebound damping.







KEEP GOING WHEN THE ROAD ENDS

KLX® motorcycles take trail riding to the next level. With a complete lineup that offers the perfect bike for everyone, KLX is for those who ride off the map and blaze their own trails. KLX is for those who are flipping through this brochure while thinking about the next adventure. Scratch that, KLX is for those who stopped reading this to get out and play.













All trademarks, registered trademarks, logos, and copyrights are the property of their respective owners.





WHEELS & BRAKES

Full-size wheels allow a generous 12 inches of ground clearance and with Dunlop® MX52 tires, the KLX®300R motorcycle is ready to take on off-road terrain. Strong disc brakes add even more confidence and control, with a twin-piston caliper gripping a 270mm disc in the front and a 240mm disc in the rear.


TRAIL-TESTED SUSPENSION

A 43mm inverted telescopic front fork provides light handling and optimum stability while the rear Uni-Trak® single-shock system features preload adjustability along with adjustable compression and rebound damping to suit a wide variety of terrain, riders and preferences.



ADVENTURE BEYOND THE MAP

The KLX®250 dual-sport motorcycle can't be contained by the street or the trails. With this dual-sport, versatility is the name of the game. Exceptional on- and off-road capability lets a wide range of riders tackle a wide range of terrain.



CAPABLE CHASSIS

A light curb weight, ample ground clearance and full-sized wheels and tires work together to tackle tough trails and roads.

PLUSH SUSPENSION

A long-travel telescopic front fork complements the rear Uni-Trak® suspension, providing a superior ride on both trails and smooth pavement.







RUGGED CHASSIS

New perimeter frame and short wheelbase offer the handling needed for confident trail riding for a wide range of riders. The frame, seat and tank were designed to give riders an easier grip, offering superior chassis control. Seams between the shrouds, seat, and side covers are flush, which facilitates freedom of movement when changing riding positions.

VERSATILE SUSPENSION

Long-travel suspension provides ample ground clearance, with a 37mm telescopic front fork and rear Uni-Trak® single-shock suspension. Maintain comfort and control even on rough terrain and adjust the shock preload to suit rider size and preference.









KLX®140G

EXTEND THE PLAY

If you're looking to up your game, the KLX®140G off-road motorcycle is for you. This full-size machine is built for full-size adventures. Durable and light in weight, this thrill seeker means business.



EXTREME LIGHT WEIGHT

Ride with confidence on the motorcycle that features a class-leading lightweight chassis.

FULL-SIZE CAPABILITY

Full-size wheels, adjustable long travel suspension and ample ground clearance means major capability, which means big time fun.









EXPLORE OFF THE MAP

The KLX®140 and KLX®140L motorcycles take off-road riding for youth riders to the next level. With a low seat height, electric start and confident handling, the KLX140 and KLX140L make for the perfect trailblazers.





PLAYFUL POWER

Ideal for off-road fun, the compact air-cooled 144cc four-stroke engine provides smooth power delivery. A five-speed gearbox with manual clutch enables rider-active response across a broad range of power that is easy to control.

LIGHTWEIGHT CHASSIS

The box-style perimeter frame is made from high-tensile steel, providing exceptional rigidity and strength, while the narrow profile contributes to confident handling by facilitating ease of rider movement.

STRONG BRAKES

A 220mm front petal disc with a dual-piston caliper is complemented by a 186mm rear petal disc, offering smooth, progressive stopping power.

KLX®140 FAMILY



KLX®110 KLX®110L

THERE'S FUN FOR EVERYONE

Even the younger riders. The KLX®110 and KLX®110L motorcycles are built with versatile performance to take on the trails. There is no better introduction to off-road riding.



VERSATILE ENGINE

Powered by a 112cc air-cooled four-stroke engine, the KLX®110 motorcycle comes with a four-speed transmission with automatic clutch while the KLX®110L motorcycle offers a manual clutch so young riders can learn big bike shifting techniques.

EASY TO LEARN

The KLX®110 motorcycle features electric start and will only start up in neutral. An adjustable screw-type throttle limiter helps parents limit the throttle opening, so the speed increases with the rider's skill.





KLX®230 ACCESSORIES

Put a personal touch on your Kawasaki KLX® motorcycle with Kawasaki Genuine Accessories, designed to provide functional, reliable and versatile performance. Customize your ride with a perfectly integrated fit, easy installation and long-lasting dependability.

Check out Kawasaki.com or visit your local dealer to view all KLX® motorcycle accessories.

























		КХ™450	КХ™250	КХ™100
ENGINE AND TRANSMISSION	ENGINE	4-stroke single, DOHC, liquid-cooled	4-stroke single, DOHC, liquid-cooled	2-stroke single with exhaust power valve, liquid-cooled
	DISPLACEMENT	449cc	249cc	99cc
	FUEL SYSTEM	DFI® with 44mm Keihin throttle body	DFI® with 44mm Keihin throttle body and dual injectors	28mm Keihin carburetor
	TRANSMISSION	5-speed, return shift, with wet multi- disc manual clutch and hydraulic clutch actuation	5-speed, return shift, with wet multi- disc manual clutch	6-speed, return shift, with wet multi- disc manual clutch
ON	FRONT SUSPENSION / WHEEL TRAVEL	49mm inverted telescopic coil- spring fork with 16-way compression damping and 16-way rebound damping/12.0 in	48mm inverted telescopic coil spring fork with 23-way compression damping and 20-way rebound damping/12.4 in	36mm inverted telescopic cartridge fork with 20-way compression damping/10.8 in
SUSPENSION	REAR SUSPENSION / WHEEL TRAVEL	Uni-Trak® gas charged shock with piggyback reservoir with dual-range (4 turns stepless high speed/19-way low-speed) compression damping, 38-way rebound damping and adjustable preload/12.1 in	Uni-Trak® gas charged shock with piggyback reservoir with dual range (2 1/16 turns stepless high speed /21-way low speed) and 38-way rebound damping and adjustable spring preload/12.2 in	Uni-Trak® gas charged shock with piggyback reservoir with 24-way compression and 21-way rebound damping plus adjustable spring preload/10.8 in
	FRONT TIRE	80/100-21	80/100-21	70/100-19
KES	REAR TIRE	120/80-19	100/90-19	90/100-16
TIRES AND BRAKES	FRONT BRAKES	Single semi-floating 270mm Braking® petal disc with dual-piston caliper	Single semi-floating 270mm Braking® petal disc with dual-piston caliper	Single 220mm petal disc with dual- piston caliper
	REAR BRAKES	Single 250mm Braking® petal disc with single-piston caliper	Single 250mm Braking® petal disc with single-piston caliper	Single 220mm petal disc with single- piston caliper
	GROUND CLEARANCE	13.4 in	13.1 in	13.0 in
TIES	SEAT HEIGHT	37.6 in	37.3 in	34.3 in
CAPAC	CURB WEIGHT	232.3 lb without fuel / 242.4 lb**	221.1 lb without fuel / 231.4 lb**	169.7 lb**
AND	FUEL CAPACITY	1.64 gal	1.69 gal	1.32 gal
SIONS	WARRANTY	Not Available	Not Available	Not Available
DIMENSIONS AND CAPACI	KAWASAKI PROTECTION PLUS™ (OPTIONAL)	Not Available	Not Available	Not Available







		КХ™85	КХ™65	KLX [®] 300R
SUSPENSION ENGINE AND TRANSMISSION	ENGINE	2-stroke single with exhaust power valve, liquid-cooled	2-stroke single with exhaust power valve, liquid-cooled	4-stroke single, DOHC, liquid- cooled
	DISPLACEMENT	84cc	64cc	292cc
	FUEL SYSTEM	28mm Keihin carburetor	24mm Mikuni carburetor	DFI® with 34mm Keihin throttle body
	TRANSMISSION	6-speed, return shift, with wet multi-disc manual clutch	6-speed, return shift, with wet multi-disc manual clutch	6-speed, return shift with wet multi-disc manual clutch
	FRONT SUSPENSION / WHEEL TRAVEL	36mm inverted telescopic cartridge fork with 20-way compression damping/10.8 in	33mm leading axle telescopic fork with 4-way rebound damping/8.3 in	43mm inverted telescopic fork with adjustable compression damping /11.2 in
	REAR SUSPENSION / WHEEL TRAVEL	Uni-Trak® single shock system with 24-way compression and 21-way rebound damping, plus adjustable spring preload/10.8 in	Uni-Trak® single shock system with 4-way rebound damping and fully adjustable spring preload/9.4 in	Uni-Trak® gas charged shock with piggyback reservoir with adjustable compression, rebound damping and spring preload/11.2 in
	FRONT TIRE	70/100-17	60/100-14	80/100-21
AKES	REAR TIRE	90/100-14	80/100-12	100/100-18
TIRES AND BRAKES	FRONT BRAKES	Single 220mm petal disc with dual-piston caliper	Single 180mm disc with single- piston caliper	Single 270mm petal disc with a dual-piston caliper
TIRE	REAR BRAKES	Single 220mm petal disc with single-piston caliper	Single 180mm disc with single- piston caliper	Single 240mm petal disc with single-piston caliper
	GROUND CLEARANCE	11.4 in	12.0 in	12.0 in / 11.8 CA model
ITIES	SEAT HEIGHT	32.7 in	29.9 in	36.4 in
CAPACITIES	CURB WEIGHT	165.3 lb**	132.2 lb**	282.2 lb / 286.6 lb. CA model**
S AND (FUEL CAPACITY	1.32 gal	1.0 gal	2.1 gal
SIONS	WARRANTY	Not Available	Not Available	6 Months
DIMENSIONS AND	KAWASAKI PROTECTION PLUS™ (OPTIONAL)	Not Available	Not Available	12, 24, or 36 months

^{**}Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). When equipped, California evaporative emissions equipment adds approximately 2.2 lb.

Specifications subject to change; full specifications available on Kawasaki.com.







		KLX [®] 250	KLX [®] 230 ABS	KLX [®] 230R
			Also available in non-ABS.	
ENGINE AND TRANSMISSION	ENGINE	4-stroke single, DOHC, liquid- cooled	4-stroke single, SOHC, air-cooled	4-stroke single, SOHC, air-cooled
	DISPLACEMENT	249cc	233cc	233cc
	FUEL SYSTEM	DFI® with 34mm Keihin throttle body	DFI® with 32mm Keihin throttle body	DFI® with 32mm Keihin throttle body
	TRANSMISSION	6-speed, return shift with wet multi-disc manual clutch	6-speed, return shift with wet multi-disc manual clutch	6-speed, return shift with wet multi-disc manual clutch
SUSPENSION	FRONT SUSPENSION / WHEEL TRAVEL	43mm inverted telescopic fork with 16-way compression damping /10 in	37mm telescopic fork/8.7 in	37mm telescopic fork/9.8 in
	REAR SUSPENSION / WHEEL TRAVEL	Uni-Trak® linkage system and single shock with 16-way compression and rebound damping and adjustable spring preload/8.8 in	Uni-Trak® linkage system and single shock with adjustable spring preload/8.8 in	Uni-Trak® linkage system and single shock with adjustable spring preload/9.9 in
	FRONT TIRE	2.75 x 21	2.75 x 21	80/100-21
TIRES AND BRAKES	REAR TIRE	4.10 x 18	4.10 x 18	100/100-18
	FRONT BRAKES	Single 265mm petal disc with a dual-piston caliper	Single 265mm petal disc with a dual-piston caliper	Single 240mm petal disc with a dual-piston caliper
	REAR BRAKES	Single 220mm petal disc with single-piston caliper	Single 220mm petal disc with single-piston caliper	Single 220mm petal disc with single-piston caliper
DIMENSIONS AND CAPACITIES	GROUND CLEARANCE	11.2 in.	10.4 in.	11.8 in
	SEAT HEIGHT	35.0 in.	34.8 in.	36.2 in
	CURB WEIGHT	304.3 lb. / 306.5 lb. CA model**	293.3 lb. / 297.7 lb. CA model**	253.6 lb / 258 lb. CA model**
	FUEL CAPACITY	2.0 gal.	2.0 gal.	1.7 gal
SIONS	WARRANTY	12 Months	12 Months	6 Months
DIMEN	KAWASAKI PROTECTION PLUS™ (OPTIONAL)	12, 24, or 36 months	12, 24, or 36 months	12, 24, or 36 months

^{**}Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). When equipped, California evaporative emissions equipment adds approximately 2.2 lb.

Specifications subject to change; full specifications available on Kawasaki.com.







KLX®140L shown

		KEK TIOE SHOWIN	KEX TIGE SHOWII
	KLX®140G	KLX [®] 140/140L	KLX [®] 110/110L
ENGINE	4-stroke single, SOHC, air-cooled	4-stroke single, SOHC, air-cooled	4-stroke single, SOHC, air-cooled
DISPLACEMENT	144cc	144cc	112cc
DISPLACEMENT FUEL SYSTEM TRANSMISSION	20mm Keihin carburetor	20mm Keihin carburetor	18mm Keihin carburetor and screw type throttle limiter on grip housing
TRANSMISSION	5-speed, return shift, with wet multi- disc manual clutch	5-speed, return shift, with wet multi- disc manual clutch	4-speed, return shift, wet multi-disc manual clutch (KLX110L) / 4-speed, return shift, automatic centrifugal and wet, multi-disc clutch (KLX110)
FRONT SUSPENSION / WHEEL TRAVEL	33mm telescopic fork/7.5 in	33mm telescopic fork/7.1 in	30mm hydraulic telescopic fork/5.5 in (KLX110L) / 30mm hydraulic telescopic fork/4.3 in (KLX110)
REAR SUSPENSION / WHEEL TRAVEL	Uni-Trak® linkage system and single shock with piggyback reservoir, 22- way rebound damping and threaded preload adjustability/7.9 in	Uni-Trak® linkage system and single shock with piggyback reservoir, fully adjustable preload and 22-way rebound damping/7.1 in (KLX140L) / Uni-Trak® linkage system and single shock with 5-way preload adjustability/7.1 in (KLX140)	Swingarm with single hydraulic shock/5.2 in (KLX110L) / Swingarm with single hydraulic shock/4.3 in (KLX110)
FRONT TIRE	2.75x21	70/100-19 (KLX140L) / 70/100-17 (KLX140)	2.50-14
REAR TIRE FRONT BRAKES	4.10x18	90/100-16 (KLX140L) / 90/100-14 (KLX140)	3.00-12
FRONT BRAKES	Single 220mm petal disc with a dual- piston caliper	Single 220mm petal disc with a dual- piston caliper	90mm mechanical drum, cable actuated
REAR BRAKES	Single 186mm petal disc with single- piston caliper	Single 186mm petal disc with single- piston caliper	110mm mechanical drum, rod actuated
GROUND CLEARANCE	12.4 in	10.0 in (KLX140L) / 9.3 in (KLX140)	10.4 in (KLX110L) / 8.5 in (KLX110)
SEAT HEIGHT	33.9 in	31.5 in (KLX140L) / 30.7 in (KLX140)	28.7 in (KLX110L) / 26.8 in (KLX110)
CURB WEIGHT	218.2 lb**	209.4 lb (KLX140L) / 205.0 lb (KLX140)**	167.5 lb**
FUEL CAPACITY	1.5 gal	1.5 gal	1.0 gal
WARRANTY	6 Months	6 Months	6 Months
CURB WEIGHT FUEL CAPACITY WARRANTY KAWASAKI PROTECTION PLUS™ (OPTIONAL)	12, 24, or 36 months	12, 24, or 36 months	12, 24, or 36 months

^{**}Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). Specifications subject to change; full specifications available on Kawasaki.com.



LIMITED WARRANTY

The Kawasaki KLX®250 and KLX®230 dual-sport models come with a 12-month limited warranty. The KLX®300R, KLX®230R, KLX®140G, KLX®140L, KLX®140, KLX®110L and KLX®110 off-road models come with a 6-month limited warranty. KX™ models are designed for closed course competition and are not covered under warranty and Kawasaki Protection Plus™ is not available.

UP TO THREE YEARS ADDITIONAL COVERAGE

Let Kawasaki protect your new KLX motorcycle for years to come with Kawasaki Protection Plus™. This plan repairs or replaces covered components free of charge if found defective in material or workmanship. Everything about the plan is easy. There's no deductible. It's honored at every authorized Kawasaki motorcycle dealer nationwide. It's transferable to another owner with no fee. Just ask your dealer how you can buy additional coverage of 12, 24, or 36 months (depending on the model and plan purchased). FL Lic #65500, Kawasaki Motors Corp., U.S.A., PO Box 25252, Santa Ana, CA 92799, (949) 770-0400.

KAWASAKI CARES

Ride responsibly. Always wear a helmet, eye protection, and proper apparel. Never ride under the influence of drugs or alcohol. Riding is more fun on a well-maintained motorcycle. Remember, riding safe is smart. Professional rider shown on a closed course. KLX®110, KLX®110L, KLX®140 and KLX®140L riders are shown on a closed course under adult supervision. ©2019 Kawasaki Motors Corp., U.S.A.



Kawasaki subscribes to the guidelines of Tread Lightly!® a program dedicated to protecting the great outdoors through education and fostering responsible enjoyment of public lands.

All trademarks, registered trademarks, logos, and copyrights are the property of their respective owners. Accessorized model shown. Printed in the U.S.A. 99960-3784

